


## 1C95X – Metric female swivel heavy series with O-ring




**MATERIAL** Nipple: very high strength carbon steel, zinc plated  
Shell and nut: high strength carbon steel, zinc plated

#	⊙				⌚	A	B	J	↻	
	DN	size	mm	inch					MPa	psi
1C95X-12-05	8	-05	7.9	5/16	M20x1.5	72	28	27	210	30,450
1C95X-16-08	12	-08	12.7	1/2	M24x1.5	87	34	32	180	26,100
1C95X-25-12	20	-12	19	3/4	M36x2	92	39	46	140	20,300

Fittings for hydraulic applications

## 1AY5X – Type “M” female swivel



**MATERIAL** Nipple: very high strength carbon steel, zinc plated  
Shell and nut: high strength carbon steel, zinc plated

#	⊙				⌚	A	B	J	↻	
	DN	size	mm	inch					MPa	psi
1AY5X-6-03	5	-03	4.8	3/16	9/16 - 18UNF	66	26	22	250	36,250
1AY5X-8-05	8	-05	7.9	5/16	3/4 - 16UNF	69	25	27	210	30,450
1AY5X-11-08	12	-08	12.7	1/2	1 - 12UNF	80	27	32	180	26,100
1AY5X-16-12	20	-12	19	3/4	1 5/16 - 12UNF	82	29	41	140	20,300

Fittings for hydraulic applications